

## **BIM STRUCTURED DATA SHEET REF 24**

Structured Data\_isoweld\_BS-S-4,8\_Nov-17\_GB\_v1

				Structured Data_Isoweld_B5-5-4,8_Nov-17_GB_
itle Block	Template Category	Self Drilling Fasteners - FR		
tle Block	Category Description	Fasteners suitable for self drilling and threadforming in Flat Roo	of application	ns
tle Block	Template Version	1		
iio Biook	Tompiato Volcion	·		
		For fastening insulation & single ply membrane to steel/ timber/	OSB3 decks	<ul> <li>These connections are for external applications &amp; used in</li> </ul>
tle Block	Suitability of Use	conjunction with thermally broken sleeves & stress plate FI-P-1	6,0. Their us	e comprises connections with predominatly static loads.
itle Block	Parameter Name/ Question	Value/ Answer	Units	Notes
anufacturers Data	Manufacturer	SFS intec Ltd	Text	
anufacturers Data	Manufacturer Website	www.sfsintec.co.uk	URL	
anufacturers Data	Product Range	Isoweld	Text	
anufacturers Data	Fastener Product Name	BS-S-4.8	Text	
anufacturers Data	Thermally Broken Insulation Sleeve Product Name	R75	Text	For insulation board corners were specified by SFS
anufacturers Data	Thermally Broken Membrane Sleeve Product Name	FI-R-20	Text	For use with FI-P-16,0 thermally broken membrane sleeves
anufacturers Data	Insulation Stress Plate Name	N/A	Text	
anufacturers Data	Membrane Stress Plate Name	FI-P-16,0-PVC / TPO	Text	Use of PVC or TPO type is dependent on membrane used
anufacturers Data	Product Literature	SFS intec catalogue	URL	
anufacturers Data	Features	For the fastening of insulation or single ply membrane to Steel or timber / OSB3 decks.	Text	
anufacturers Data	ISO 9001	www.sfsintec.co.uk/quallity_management	URL	
anufacturers Data	CE Mark	Yes	Text	
anufacturers Data	FM Approval	Yes	Text	
anufacturers Data	SINTEF Approval	Yes	Text	
oplication Data	Flat, Mono Pitch, Duopitch or Barrell roof	Flat, Mono Pitch, Duopitch or Barrell	Text	
oplication Data	System Type	Flat Roof membrane & Insulation attachment	Text	
plication Data	Membrane attachment type	Field fixing of membrane fasteners which are welded to membrane.	Text	
oplication Data	Deck type	Steel (min 0,63mm),Timber (min 22mm) OSB3/Plywood (Min 18mm)	Text	
oplication Data	Environmental Corrosion Category to BS EN12944	C3	Text	
oplication Data	Estimated Service Life C3 (BS ISO 15686-1:2011)	20	Up to Years	
pplication Data	Warranty C3	20	Years	
imensional Data	Fastener Thread Diameter	4.0	T	
imensional Data	Fastener Head Diameter	4,8 8,9	mm	
imensional Data	Fastener Drive Position	External	mm Text	
imensional Data	Fastener Head Style	Torx25-32	Text	
imensional Data	Fastener Length	60, 80, 100, 120, 140, 160, 180, 200	mm	
inchisional Data	i asterici Longui			
	· ·			
imensional Data	Effective Fastener Thread Length		mm	
	Effective Fastener Thread Length Fastener Drilling Capacity - Aluminium	75	mm mm	
imensional Data	Fastener Drilling Capacity - Aluminium	75 N/A	mm mm mm	
imensional Data imensional Data		75	mm mm	
imensional Data imensional Data imensional Data	Fastener Drilling Capacity - Aluminium Fastener Drilling Capacity - Steel	75 N/A 2x1.00 75	mm mm mm mm	
mensional Data mensional Data mensional Data mensional Data	Fastener Drilling Capacity - Aluminium Fastener Drilling Capacity - Steel Thermally Broken Insulation Sleeve washer dimension	75 N/A 2x1.00	mm mm mm mm	
mensional Data mensional Data mensional Data mensional Data mensional Data	Fastener Drilling Capacity - Aluminium Fastener Drilling Capacity - Steel Thermally Broken Insulation Sleeve washer dimension Thermally Broken Insulation Sleeve Lengths	75 N/A 2x1.00 75 35, 65, 85, 105, 135, 165, 185, 225, 255, 285	mm mm mm mm mm	
mensional Data	Fastener Drilling Capacity - Aluminium Fastener Drilling Capacity - Steel Thermally Broken Insulation Sleeve washer dimension Thermally Broken Insulation Sleeve Lengths Thermally Broken Membrane Sleeve washer dimension Thermally Broken Membrane Sleeve Lengths Insulation Stress Plate Dimension	75 N/A 2x1.00 75 35, 65, 85, 105, 135, 165, 185, 225, 255, 285 20 40,70.100,130,160,190,230,300 N/A	mm mm mm mm mm mm	
mensional Data	Fastener Drilling Capacity - Aluminium Fastener Drilling Capacity - Steel Thermally Broken Insulation Sleeve washer dimension Thermally Broken Insulation Sleeve Lengths Thermally Broken Membrane Sleeve washer dimension Thermally Broken Membrane Sleeve Lengths	75 N/A 2x1.00 75 35, 65, 85, 105, 135, 165, 185, 225, 255, 285 20 40,70.100,130,160,190,230,300	mm mm mm mm mm mm mm	Diameter
mensional Data mensional Data mensional Data mensional Data mensional Data mensional Data mensional Data mensional Data	Fastener Drilling Capacity - Aluminium Fastener Drilling Capacity - Steel Thermally Broken Insulation Sleeve washer dimension Thermally Broken Insulation Sleeve Lengths Thermally Broken Membrane Sleeve washer dimension Thermally Broken Membrane Sleeve Lengths Insulation Stress Plate Dimension Membrane Stress Plate Dimension	75 N/A 2x1.00 75 35, 65, 85, 105, 135, 165, 185, 225, 255, 285 20 40,70.100,130,160,190,230,300 N/A 80	mm mm mm mm mm mm mm mm mm	Diameter
mensional Data	Fastener Drilling Capacity - Aluminium Fastener Drilling Capacity - Steel Thermally Broken Insulation Sleeve washer dimension Thermally Broken Insulation Sleeve Lengths Thermally Broken Membrane Sleeve washer dimension Thermally Broken Membrane Sleeve Lengths Insulation Stress Plate Dimension Membrane Stress Plate Dimension  European Technical Approval (ETA)	75 N/A 2x1.00 75 35, 65, 85, 105, 135, 165, 185, 225, 255, 285 20 40,70.100,130,160,190,230,300 N/A	mm mm mm mm mm mm mm mm mm	Diameter
mensional Data	Fastener Drilling Capacity - Aluminium Fastener Drilling Capacity - Steel Thermally Broken Insulation Sleeve washer dimension Thermally Broken Insulation Sleeve Lengths Thermally Broken Membrane Sleeve washer dimension Thermally Broken Membrane Sleeve Lengths Insulation Stress Plate Dimension Membrane Stress Plate Dimension  European Technical Approval (ETA) Declaration of Performance (DoP)	75 N/A 2x1.00 75 35, 65, 85, 105, 135, 165, 185, 225, 255, 285 20 40,70.100,130,160,190,230,300 N/A 80  ETA-08/0262	mm	Diameter
mensional Data acchnical Data acchnical Data acchnical Data	Fastener Drilling Capacity - Aluminium Fastener Drilling Capacity - Steel Thermally Broken Insulation Sleeve washer dimension Thermally Broken Insulation Sleeve Lengths Thermally Broken Membrane Sleeve washer dimension Thermally Broken Membrane Sleeve Lengths Insulation Stress Plate Dimension Membrane Stress Plate Dimension  European Technical Approval (ETA) Declaration of Performance (DoP) Fastener Surface Coating	75 N/A 2x1.00 75 35, 65, 85, 105, 135, 165, 185, 225, 255, 285 20 40,70.100,130,160,190,230,300 N/A 80  ETA-08/0262 N/A	mm	Diameter
mensional Data achnical Data achnical Data achnical Data achnical Data	Fastener Drilling Capacity - Aluminium Fastener Drilling Capacity - Steel Thermally Broken Insulation Sleeve washer dimension Thermally Broken Insulation Sleeve Lengths Thermally Broken Membrane Sleeve washer dimension Thermally Broken Membrane Sleeve Lengths Insulation Stress Plate Dimension Membrane Stress Plate Dimension  European Technical Approval (ETA) Declaration of Performance (DoP) Fastener Surface Coating Fastener Material	75 N/A 2x1.00 75 35, 65, 85, 105, 135, 165, 185, 225, 255, 285 20 40,70.100,130,160,190,230,300 N/A 80  ETA-08/0262 N/A Stainless Steel	mm	Diameter
mensional Data	Fastener Drilling Capacity - Aluminium Fastener Drilling Capacity - Steel Thermally Broken Insulation Sleeve washer dimension Thermally Broken Insulation Sleeve Lengths Thermally Broken Membrane Sleeve washer dimension Thermally Broken Membrane Sleeve Lengths Insulation Stress Plate Dimension Membrane Stress Plate Dimension  European Technical Approval (ETA) Declaration of Performance (DoP) Fastener Surface Coating Fastener Material Fastener Material	75 N/A 2x1.00 75 35, 65, 85, 105, 135, 165, 185, 225, 255, 285 20 40,70.100,130,160,190,230,300 N/A 80  ETA-08/0262 N/A Stainless Steel 316, Grade A4	mm the control of	Diameter
mensional Data echnical Data	Fastener Drilling Capacity - Aluminium Fastener Drilling Capacity - Steel Thermally Broken Insulation Sleeve washer dimension Thermally Broken Insulation Sleeve Lengths Thermally Broken Membrane Sleeve washer dimension Thermally Broken Membrane Sleeve Lengths Insulation Stress Plate Dimension Membrane Stress Plate Dimension  European Technical Approval (ETA) Declaration of Performance (DoP) Fastener Surface Coating Fastener Material Fastener Material Grade Fastener Material Grade to EN standard	75 N/A 2x1.00 75 35, 65, 85, 105, 135, 165, 185, 225, 255, 285 20 40,70.100,130,160,190,230,300 N/A 80  ETA-08/0262 N/A Stainless Steel 316, Grade A4 1.4401	mm	Diameter
mensional Data chnical Data	Fastener Drilling Capacity - Aluminium Fastener Drilling Capacity - Steel Thermally Broken Insulation Sleeve washer dimension Thermally Broken Insulation Sleeve Lengths Thermally Broken Membrane Sleeve washer dimension Thermally Broken Membrane Sleeve Lengths Insulation Stress Plate Dimension Membrane Stress Plate Dimension  European Technical Approval (ETA) Declaration of Performance (DoP) Fastener Surface Coating Fastener Material Fastener Material Grade Fastener Material Grade to EN standard Minimum Fastener Embedment into Steel Deck	75 N/A 2x1.00 75 35, 65, 85, 105, 135, 165, 185, 225, 255, 285 20 40,70.100,130,160,190,230,300 N/A 80  ETA-08/0262  N/A Stainless Steel 316, Grade A4 1,4401 20	mm the control of	Diameter
mensional Data chnical Data	Fastener Drilling Capacity - Aluminium Fastener Drilling Capacity - Steel Thermally Broken Insulation Sleeve washer dimension Thermally Broken Insulation Sleeve Lengths Thermally Broken Membrane Sleeve washer dimension Thermally Broken Membrane Sleeve Washer dimension Thermally Broken Membrane Sleeve Lengths Insulation Stress Plate Dimension Membrane Stress Plate Dimension  European Technical Approval (ETA) Declaration of Performance (DoP) Fastener Surface Coating Fastener Material Fastener Material Fastener Material Grade Fastener Material Grade to EN standard Minimum Fastener Embedment into Steel Deck Minimum Fastener Embedment into Timber / OSB3 Deck	75 N/A 2x1.00 75 35, 65, 85, 105, 135, 165, 185, 225, 255, 285 20 40,70.100,130,160,190,230,300 N/A 80  ETA-08/0262 N/A Stainless Steel 316, Grade A4 1.4401 20 30	mm	Diameter
mensional Data chnical Data	Fastener Drilling Capacity - Aluminium Fastener Drilling Capacity - Steel Thermally Broken Insulation Sleeve washer dimension Thermally Broken Insulation Sleeve Lengths Thermally Broken Membrane Sleeve washer dimension Thermally Broken Membrane Sleeve washer dimension Thermally Broken Membrane Sleeve Lengths Insulation Stress Plate Dimension Membrane Stress Plate Dimension  European Technical Approval (ETA) Declaration of Performance (DoP) Fastener Surface Coating Fastener Material Fastener Material Fastener Material Grade Fastener Material Grade to EN standard Minimum Fastener Embedment into Steel Deck Minimum Fastener Embedment into Timber / OSB3 Deck Minimum Fastener Embedment into Concrete Deck	75 N/A 2x1.00 75 35, 65, 85, 105, 135, 165, 185, 225, 255, 285 20 40,70.100,130,160,190,230,300 N/A 80  ETA-08/0262 N/A Stainless Steel 316, Grade A4 1.4401 20 30 N/A	mm	
mensional Data chnical Data	Fastener Drilling Capacity - Aluminium Fastener Drilling Capacity - Steel Thermally Broken Insulation Sleeve washer dimension Thermally Broken Insulation Sleeve Lengths Thermally Broken Membrane Sleeve Washer dimension Thermally Broken Membrane Sleeve Lengths Insulation Stress Plate Dimension Membrane Stress Plate Dimension  European Technical Approval (ETA) Declaration of Performance (DoP) Fastener Surface Coating Fastener Material Fastener Material Grade Fastener Material Grade to EN standard Minimum Fastener Embedment into Steel Deck Minimum Fastener Embedment into Timber / OSB3 Deck Minimum Fastener Embedment into Concrete Deck Thermally Broken Insulation / membrane Sleeve material	75 N/A 2x1.00 75 35, 65, 85, 105, 135, 165, 185, 225, 255, 285 20 40,70.100,130,160,190,230,300 N/A 80  ETA-08/0262 N/A Stainless Steel 316, Grade A4 1.4401 20 30 N/A Polypropleyne / Polyamide	mm	Diameter  R75 is Polypropolyne & FI-R-20 is Polyamide
mensional Data	Fastener Drilling Capacity - Aluminium Fastener Drilling Capacity - Steel Thermally Broken Insulation Sleeve washer dimension Thermally Broken Insulation Sleeve Lengths Thermally Broken Membrane Sleeve washer dimension Thermally Broken Membrane Sleeve washer dimension Thermally Broken Membrane Sleeve Lengths Insulation Stress Plate Dimension Membrane Stress Plate Dimension  European Technical Approval (ETA) Declaration of Performance (DoP) Fastener Surface Coating Fastener Material Fastener Material Fastener Material Grade Fastener Material Grade to EN standard Minimum Fastener Embedment into Steel Deck Minimum Fastener Embedment into Timber / OSB3 Deck Minimum Fastener Embedment into Concrete Deck	75 N/A 2x1.00 75 35, 65, 85, 105, 135, 165, 185, 225, 255, 285 20 40,70.100,130,160,190,230,300 N/A 80  ETA-08/0262 N/A Stainless Steel 316, Grade A4 1.4401 20 30 N/A	mm	
mensional Data achnical Data	Fastener Drilling Capacity - Aluminium Fastener Drilling Capacity - Steel Thermally Broken Insulation Sleeve washer dimension Thermally Broken Insulation Sleeve Lengths Thermally Broken Membrane Sleeve Washer dimension Thermally Broken Membrane Sleeve Lengths Insulation Stress Plate Dimension Membrane Stress Plate Dimension  European Technical Approval (ETA) Declaration of Performance (DoP) Fastener Surface Coating Fastener Material Fastener Material Grade Fastener Material Grade to EN standard Minimum Fastener Embedment into Steel Deck Minimum Fastener Embedment into Timber / OSB3 Deck Minimum Fastener Embedment into Concrete Deck Thermally Broken Insulation / membrane Sleeve material	75 N/A 2x1.00 75 35, 65, 85, 105, 135, 165, 185, 225, 255, 285 20 40,70.100,130,160,190,230,300 N/A 80  ETA-08/0262 N/A Stainless Steel 316, Grade A4 1.4401 20 30 N/A Polypropleyne / Polyamide	mm	
mensional Data achnical Data	Fastener Drilling Capacity - Aluminium Fastener Drilling Capacity - Steel Thermally Broken Insulation Sleeve washer dimension Thermally Broken Insulation Sleeve Lengths Thermally Broken Membrane Sleeve washer dimension Thermally Broken Membrane Sleeve Washer dimension Thermally Broken Membrane Sleeve Lengths Insulation Stress Plate Dimension Membrane Stress Plate Dimension  European Technical Approval (ETA) Declaration of Performance (DoP) Fastener Surface Coating Fastener Material Fastener Material Fastener Material Grade Fastener Material Grade to EN standard Minimum Fastener Embedment into Steel Deck Minimum Fastener Embedment into Timber / OSB3 Deck Minimum Fastener Embedment into Concrete Deck Thermally Broken Insulation / membrane Sleeve material Insulation / Membrane Stress plate Material Grade	75 N/A 2x1.00 75 35, 65, 85, 105, 135, 165, 185, 225, 255, 285 20 40,70.100,130,160,190,230,300 N/A 80  ETA-08/0262 N/A Stainless Steel 316, Grade A4 1.4401 20 30 N/A Polypropleyne / Polyamide Adhesive Coated Carbon Steel	mm	
mensional Data	Fastener Drilling Capacity - Aluminium Fastener Drilling Capacity - Steel Thermally Broken Insulation Sleeve washer dimension Thermally Broken Insulation Sleeve Lengths Thermally Broken Membrane Sleeve washer dimension Thermally Broken Membrane Sleeve Lengths Thermally Broken Membrane Sleeve Lengths Insulation Stress Plate Dimension Membrane Stress Plate Dimension  European Technical Approval (ETA) Declaration of Performance (DoP) Fastener Surface Coating Fastener Material Fastener Material Grade Fastener Material Grade to EN standard Minimum Fastener Embedment into Steel Deck Minimum Fastener Embedment into Timber / OSB3 Deck Minimum Fastener Embedment into Concrete Deck Thermally Broken Insulation / membrane Sleeve material Insulation / Membrane Stress plate Material Grade	75 N/A 2x1.00 75 35, 65, 85, 105, 135, 165, 185, 225, 255, 285 20 40,70.100,130,160,190,230,300 N/A 80  ETA-08/0262 N/A Stainless Steel 316, Grade A4 1.4401 20 30 N/A Polypropleyne / Polyamide Adhesive Coated Carbon Steel	mm	
imensional Data echnical Data expensive the properties of the properties o	Fastener Drilling Capacity - Aluminium Fastener Drilling Capacity - Steel Thermally Broken Insulation Sleeve washer dimension Thermally Broken Insulation Sleeve Lengths Thermally Broken Membrane Sleeve washer dimension Thermally Broken Membrane Sleeve Lengths Thermally Broken Membrane Sleeve Lengths Insulation Stress Plate Dimension Membrane Stress Plate Dimension  European Technical Approval (ETA) Declaration of Performance (DoP) Fastener Surface Coating Fastener Material Fastener Material Grade Fastener Material Grade to EN standard Minimum Fastener Embedment into Steel Deck Minimum Fastener Embedment into Timber / OSB3 Deck Minimum Fastener Embedment into Concrete Deck Thermally Broken Insulation / membrane Sleeve material Insulation / Membrane Stress plate Material Grade	75 N/A 2x1.00 75 35, 65, 85, 105, 135, 165, 185, 225, 255, 285 20 40,70.100,130,160,190,230,300 N/A 80  ETA-08/0262 N/A Stainless Steel 316, Grade A4 1.4401 20 30 N/A Polypropleyne / Polyamide Adhesive Coated Carbon Steel	mm	

The details stated are results of tests and/or calculations and therefore are non-binding and do not represent guaranties or warranted characteristics for none-specified applications. All calculations therefore have to be checked and approved by the responsible planner ahead of execution. The user is responsible to assure compliance with all applicable laws and regulations.